

请在下订单前确认下记事项(订单确认清单)

When ordering capacitor, please provide information on the items below :Ordering Check list

| 区分 Class | 事项 Item | 事例 Examples | 确认/希望内容 Spsecifications |
|----------------------------|---|---|----------------------------|
| 规格 Rating | 额定电压Rated Voltage | 50VDC, 250VAC etc. | |
| | 标准容量Capacitance | 100PF, 0.1 μ F etc. | |
| | 容量的偏差Capacitance Tolerance | $\pm 5\%$, $\pm 10\%$, $\pm 20\%$ etc. | |
| 使用条件 Conditions | 使用机种Applied Equipment | 电视, 微波炉, 照明器具等 TV, Microwave oven, Car, Lighting apparatus etc. | |
| | 使用回路, 目的 Applied Circuit, Purpose | S字补正, 时钟电路 TV horizontal deflection circuit, Snubber circuit,etc. | |
| | 环境条件Environment | 室内、室外、浴室、寒冷的区域等 In-house, Outdoor, Bathroom, Cold district etc. | |
| | 使用温度Temperature | - 10 $^{\circ}$ C ~ +60 $^{\circ}$ C | |
| | 使用湿度Humidity | 5%~75%RH etc. | |
| | 施加电压Applied Voltage | 100Vrms,125V0-p,25VDC | |
| | 电压波形Voltage Waveform | 正弦波, 矩形波, 半波, 脉冲等 Sinusoidal wave, Half wave,Full wave, Rectangular wave, Pulse etc. | |
| | 通电电流Current | 10mArms, 3Ap-p,50A0-p | |
| | 电流波形Current Waveform | 正弦波, 锯齿波脉冲等 Sinusoidal wave,Sawtooth type wave,Pulse etc. | |
| | 使用频率Frequency | 50Hz, 100KHz | |
| | 自己温度上升Self Temperature-rise | 85 $^{\circ}$ C, 105 $^{\circ}$ C等 (电容器表温-环境温度=自己温升) 85 $^{\circ}$ C, 105 $^{\circ}$ Cetc.(Self temperature-rise=Capacitor surface temperature-Ambient temperature) | |
| 温度系数Temperature Coeffident | "-150ppm/ $^{\circ}$ C, +200ppm/ $^{\circ}$ C etc. | | |
| 安装 Mounting | 安装方法Mounting Method | 手插入, 自动插入Manual, Automatic | |
| | 安装机Mounting Machine | 松下R ^{HU} 等 Panasert R ^{HU} etc. | |
| 焊接 Soldering | 作业方法Method | 手焊接自动焊接(波峰焊,回流焊)等 Manual,Automatic etc. | |
| | 作业条件Conditions | 温度260 $^{\circ}$ C, 浸4sec, 往返2回等 Temperature 260 $^{\circ}$ C, Dipping time 4 sec, Repeating times 2 time etc. | |
| | 予加热条件Preheat Conditions | 加热方式,时间,温度等Heat method,Temperature,Time etc. | |
| | 洗净剂Detergent | 氟利昂等具体的品名Freon substitute etc.Specify the name | |
| | 清洗方法Cleanig Method | 浸泡, 超声波清洗机等Soaking,Ultrasonic etc. | |
| | 清洗条件Cleaning Conditions | 手浸泡5分钟, 干燥5分钟等 5 min.dipping, 5 min. drying etc. | |
| 尺寸、形状 Shape/Size | 形状Shape | 盒式, 树脂包封等 Coated, Cased etc. | |
| | 尺寸Size | L * H * T F(引线间距)等 L * H * T F(Lead-pitch)etc. | |
| | 端子加工Terminal Form | 直线, 切腿, 加工, 编带等 Straight,Cut,Crimped,Taping etc. | |
| 波峰焊接温度 Reflow Temp. | 预热温度, 本加热温度, 温度监控方法的等 Pre heat temp.,Main heat temp.,Temp.monitoring method etc. | | |

备注: Notes:

- 特殊品订购时, 由于关系到设备, 部品的投入及纳期, 请通知相关的信息: 试作/量产的开始时间, 计划数, 生产数/月。
- 如使用贵司特殊的部品品番号时, 请告知。
- 产品品番, 规格等会有变更, 请了解。
- 目录上记载的仕様, 材质等内容可能会无预告变更最终的仕様确定以纳入仕様书为准。

- When need specify custom type(made-to-order),new tools & jigs or new equipment might be required on our side. Your notice on development schedule and estimated quantity would help in preparation of our response to your order.
- If you designate your own part number, please let us know.
- The parts number,specifications will be changed.
- The information(specification and material etc.) described in catalog will be changed without notice. Specifications shall be agreed in written form of approval sheet.